



- FUNCTION OF INDICATOR LEDS ON PCB**
- A ● INDICATES REMOTE SEND SWITCH IS OPERATED
 - B ● INDICATES REMOTE DOOR IS CLOSED
 - C ● INDICATES LOCAL SEND SWITCH IS OPERATED
 - D ● INDICATES LOCAL DOOR IS CLOSED
 - E ● INDICATES GREEN LED IS LIT
 - F ● INDICATES RED LED IS LIT
 - G ● INDICATES REMOTE DOOR IS LOCKED
 - H ● INDICATES LOCAL GREEN LED IS LIT
 - I ● INDICATES LOCAL RED LED IS LIT
 - J ● INDICATES LOCAL DOOR IS LOCKED
 - K ● INDICATES VACUUM MOTOR IS RUNNING
 - L ● INDICATES PRESSURE MOTOR IS RUNNING
 - M ● INDICATES POWER IS ON
 - N ● BLINKING INDICATES PROGRAM IS OPERATIONAL
- CIRCUIT BOARD SHORTING BLOCKS**
- JP1 — NONE OR AS NEEDED
 - JP2 — NONE OR AS NEEDED
 - JP3 — NONE OR AS NEEDED
 - JP4 — NONE OR AS NEEDED
 - JP7 — NONE OR AS NEEDED
 - JP9 — NONE OR AS NEEDED
 - JP10 — BETWEEN PINS 1 & 2

TO SECURE GROUND LUG TO FRAME USE EXTERNAL STAR WASHER BETWEEN LUG AND FRAME AND SECURE WITH #8 SHEET METAL SCREW.
USE UL LISTED GROUND LUG.

VOLTAGE -120VAC
14 AMPS
1 HP SINGLE PHASE/50/60 HZ.
20 AMP BRANCH CIRCUIT PROTECTION TO BE PROVIDED BY OTHERS DURING FIELD INSTALLATION.

EAGLE PNEUMATIC, INC.
(863)644-4870

INFORMATION CONTAINED HEREIN IS PROPRIETARY TO EAGLE PNEUMATIC, INC. ALL RIGHTS RESERVED.

TOLERANCES:
UNLESS OTHERWISE SPECIFIED FRACTIONS +/-1/32"
DECIMALS +/--.005"

REVISONS:

2-1/15/03	7-02/10/04
3-04/10/03	
4-05/29/03	
5-06/02/03	
6-07/03/03	

DRAWN BY: JAC

DATE: 12/19/02

NAME:

WIRING DIAGRAM
38.4 INCH ULTIMATE
MARKII SYSTEM
WITH LCD

PART NO.

E-11905WD

CAD FILE: A20